ACO GULLY 218 - Bodies for 300mm grates

Part No. 141993

ACO Gully 218, adjustable height body with vertical 160mm outlet, grade 316 stainless steel

Product Features

1. Hygienic design according to EN 1672 and ISO 14159

- Deep drawn body ensures smooth contours eliminating crevices for bacterial growth
- Rounded internal corners of 3mm and 10mm to enable easy cleaning
- Drainable design
- No overlapped welds and no welded corners
- 2. Adjustable height tops to suit finished floor level

3. Solid edge in-fill


- Solid edge infill improves durability and stability with the surrounding floor, minimising floor cracks
- 4. Manufactured from grade 316 stainless steel

5. Optional accessories

- Removable foul air trap
- Removable and fixed strainers for sediment retention
- Retention chains for strainers and foul air trap

6. Hydraulic data

■ 27.1 L/s





Note: All dimensions are in mm



Specification Clause

The gully shall be ACO Gully 218, adjustable height body with vertical 160mm outlet, grade 316 stainless steel (Part No. 141993). Available with optional fixed strainer (Part No. 142008), removable strainer (Part No. 408233 or 413029) and retention chains.

Materials and Design

The gully shall be manufactured in compliance with EN 1672 Food processing machinery basic concepts, ISO 14159 Hygiene requirements for the design of machinery and EHEDG:

- The gully body shall be deep drawn to ensure rounded internal corners no less than 3mm for ease of cleaning;
- The gully shall be designed to ensure complete drainage, with no overlapped welds or welded corners;
- The gully shall come complete with solid edge infill to enhance durability when under load.



General Installation Illustration



Adjustable height gully in ground slab with resin floor finish connecting into stainless pipe and P-Trap.

- 1 Resin topping
- 2 Flexible sealant
- 3 Socketed pipe (by ACO)
- 4 P-Trap (by ACO)
- 5 Straight coupling (by ACO)
- 6 Soil
- 7 Ground slab

Note: The illustration is shown for guidance only and shows a typical drain and not necessarily the specific type described on the data sheet.

For downloadable drawings, visit www.acowexel.com.au

ACO Polycrete Pty Ltd, Australia

Ph: 1300 765 226 www.acowexel.com.au sales@acoaus.com.au

ACO Limited, New Zealand

Ph: 0800 448 080 www.acowexel.co.nz sales@aconz.co.nz

